

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ► GLASS DOOR ► WHITE PAINTED

CRG 2

GAS
R600a

50 mm

A
ENERGY CLASS

3
CLIMATIC CLASS

30°C

LED

DETAILS

Inner assistance fan

Air circulating fan assistance

Blue backlit main switch

Shelf with small distance between the line and bottom shelf fits as standard

External cylindric handle in stainless steel (Steel color for X Version)



GENERAL FEATURES

- 200 Lt. Refrigerated upright (GLASS DOOR)
- White external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (50mm per side)
- Digital Thermostat and internal LED light
- High temperature alarm
- Removable Gasket
- Reversible door
- Lock and main switch fitted as standard
- Adjustable shelves: 2 Pcs + 1 Pcs Bottom
- N.2 Adjustable feet + N.2 Rollers at the back
- Stainless steel external handle
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	200 L
Temperature	+2°C ~ +8°C
Consumption	0.871 kWh/24h
Rated Power	76 W
Noise level	40 dB(A)
Net Weight	45.5 Kg
Gross Weight	50 Kg
External Dimensions (WxDxH mm)	598x679x838
Internal Dimensions (WxDxH mm)	477x443x652
Packaging dimensions (WxDxH mm)	650x680x880
Loading quantities 20'/40'/40'HQ	48/108/162

CERTIFICATION

CE RoHS

PRODUCT DIMENSIONS

