



DISHWASHER UX-50

Rack size 500 mm x 500 mm and door clearance 380 mm. Multi-power version.



WARE WASHING
COMMERCIAL DISHWASHERS



SALES DESCRIPTION

- ✓ Sani-Control: guaranteed disinfection.
- ✓ Embedded bodywork and easy-grip door: hygienic and ergonomic.
- ✓ Exclusive Hydroblade™ washing arms: maximum effectiveness.
- ✓ 3-stage filtering system.
- ✓ Double-walled body (partial).

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: Ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.

New recessed bodywork

- ✓ Ergonomic design with rounded corners to prevent the accumulation of dirt and facilitate cleaning.
- ✓ Compact tank volume (50% water saving compared to the previous range).
- ✓ Embedded basket guides.

Hydroblade™ washing arms

- ✓ Redesigned nozzles for greater washing performance.
- ✓ The “monoblock” design delivers durability and resistance to impacts.
- ✓ 30% savings in water consumption during rinsing compared to the previous range.

3-stage filter system: surface, tank and extraction

- ✓ Keeps the washing water in optimal conditions to maintain constant washing performance.
- ✓ The surface filters feature an “easy-on” design and can be quickly removed without having to disconnect the washing arms.

“Easy grip” door: new design with integrated door handle

- ✓ The integration of the components provides greater resistance and robustness.

- ✓ Designed to have no corners or areas that are difficult to access: prevents deposits of dirt and facilitates cleaning.
- ✓ Its ergonomic handle provides a perfect grip, even with wet hands.
- ✓ Double-walled door with safety microswitch and high quality seal.
- ✓ 38 cm loading capacity: high versatility for washing a wide range of items: dishes, Euronorm trays, GN 1/1 tubs and pizza plates diam 39 cm.

Premium warewashing

- ✓ Ultra Xperience: high performance, without complications.
- ✓ Soft start: progressive start-up of the washing pump to protect fragile items.
- ✓ Colour LCD Display: intuitive communication of the machine status by means of messages, colour codes and icons.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Adaptable: allows the main parameters of the machine to be adjusted to the needs of each user.
- ✓ TEMPERATURE DISPLAY.
- ✓ Wash Plus+ function: increases the intensity of the wash cycle for greater cleaning performance
- ✓ Control panel with IP65 humidity protection.

You will never WASH ALONE

- ✓ Tech Services: our team of technicians will help you so that your machine is always ready for use.
- ✓ Design Services: tell us what your needs are and we will advise you.
- ✓ 60 years of experience and know-how at your disposal.

INCLUDES

- ✓ Rinse aid pump.
- ✓ 1 glasses basket.
- ✓ 1 mixed basket (plates).
- ✓ 1 small basket for cutlery.

OPTIONAL

- ☐ Detergent dosing kit.
- ☐ Drain pump with level sensor. Proactive tank water renewal.
- ☐ Manual resin regeneration water softener.
- ☐ Double-level accessory for washing two baskets at the same time.



SAMMIC, S.L. · Basarte, 1
20720 AZKOITIA (Gipuzkoa) · SPAIN

product sheet
updated 09/02/2026



DISHWASHER UX-50

Rack size 500 mm x 500 mm and door clearance 380 mm. Multi-power version.



WARE WASHING
COMMERCIAL DISHWASHERS

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 500 x 500 mm baskets
- ☐ Inserts & supplements
- ☐ High feet kit
- ☐ Reverse osmosis devices OS-140
- ☐ Dosing equipments front AX / UX glass- and undercounter dishwashers
- ☐ Stand for 500 x 500 mm dishwashers
- ☐ Double rack kits for AX/UX
- ☐ Drain pumps for AX / UX dishwashers

SPECIFICATIONS

Basket dimensions: 500 mm x 500 mm
Useful height: 380 mm
Cycle duration: 90 / 110 / 120 / 180 / 240"
Production baskets / hour: 40 / 33 / 30 / 20 / 15
Wash temperature: 40°C - 65°C
Rinse temperature: 65°C - 87°C
Boiler capacity: 8 l
Wash tank capacity: 14 l

Consumption and savings

Water consumption/cycle: 2.5 l
Automatic saving mode in: 25'
Automatic switch-off: 120'

Energy consumption

Consumption/cycle (kWh): 0,19 kWh
Tank filling consumption (kWh): 0,6 kWh

Loading

Pump: 750 W / 1 Hp
Tank: 1800 W
Boiler: 5000 W
Total loading: 5750 W


External dimensions (W x D x H)

✓ Width: 580 mm
✓ Depth: 635 mm
✓ Height: 835 mm
Net weight: 57 kg
Noise level (1m.): 69 dB(A)
Crated dimensions
640 x 695 x 960 mm

AVAILABLE MODELS

1303220	UX-50 400/50/3N
1303221	UX-50 220/60/1
1303225	UX-50B 220/60/1
1303234	UX-50BD 220/60/1
1303236	UX-50BD 230/50/1 (3Kw)

* Ask for special versions availability



sammic | sammic.com
Food Service Equipment Manufacturer

Polígono Basarte, 1.
20720 Azkoitia, Spain

phone +34 943 15 72 36
sales@sammic.com



Project

Date

Item

Qty

Approved

product sheet
updated 09/02/2026