

Water softening system WEH1600



- ▶ Performance capacity at 10° dH: 1600 litres / day
- ▶ Cost-effective and environmentally friendly thanks to reduction in required detergent quantity
- ▶ Monitoring the regenerated water volume with an optionally available water meter
- ▶ Reduction in lime deposits inside appliance and on washed items due to reduction in water hardness

Description

This water softening unit provides protection against calcification for commercial dishwashers and optimises washing results by reducing lime deposits on washed items. Thanks to the softer water, the use of detergents is minimised.

Features

- | | |
|----------------------------------|---|
| • Water intake temperature from: | 5 °C |
| • Water intake temperature to: | 35 °C |
| • Setting possibilities: | Brine dosing
Time
Time-based regeneration |
| • Regeneration: | Time period |
| • Operating pressure: | 3 - 6 bar |
| • Brine tank salt store: | 10 kg |
| • Salt consumption: | 0.96 kg / regeneration |
| • Regeneration time: | 95 min. |
| • Digital display: | Yes |
| • Power load: | 0.006 kW 230 V 50/60 Hz |
| • Water connection: | 3/4" |
| • Colour: | White |
| • Connection capacity: | 1 unit |
| • Output capacity: | 1,600 litres / day at 10° dH (total hardness) |
| • Designed for: | Commercial dishwashers |

▶ Continue on the next page

Water softening system WEH1600

- With active carbon: No
- Material: Plastic
- Important information: -
- Size: W 255 x D 400 x H 420 mm
- Weight: 8.6 kg



Water softening system WEH1600

Add on Products

Connecting set WEH1600



- Set comprises: 2 armoured hoses AG - water connection 3/4", length 1 m, rated width Ø 15 mm
- Important information: -
- Size: W 420 x D 325 x H 60 mm
- Weight: 1 kg

Code-No. 109885
GTIN 4015613586748