



GLASSWASHER GP-40

Rack size 400 mm x 400 mm and door clearance 240 mm.



WARE WASHING
COMMERCIAL GLASSWASHER • GLASS-PRO LINE



SALES DESCRIPTION

Sani-Control guarantee

- ✓ GUARANTEED DISINFECTION in compliance with standard DIN 10534.
- ✓ THERMAL LOCK function: ensures that rinsing will be carried out at the ideal temperature to disinfect the dishes.
- ✓ Upper and lower washing.
- ✓ Construction in stainless steel AISI 304 2B.
- ✓ Interior with rounded finishes to prevent the accumulation of dirt.

Double filter system

- ✓ Maximum protection of the washing pump.

Double-walled door

- ✓ Double-walled door, safety microswitch and high quality seal: perfectly soundproof and watertight.

Warewashing, made simple

- ✓ GP Xperience: simple and intuitive use.
- ✓ Dedicated cycles: selection of the ideal washing programme using icons.
- ✓ Electronic control panel with IP65 humidity protection.
- ✓ 100% tested.

Tech-friendly

- ✓ Tool-free extraction of diffusers and filters for maintenance and cleaning.
- ✓ Easy access to components for repair.

INCLUDES

- ✓ Rinse aid pump.
- ✓ 1 mixed basket (plates).
- ✓ 1 glasses basket.
- ✓ 1 small basket for cutlery.

OPTIONAL

- ☐ Detergent dosing kit.
- ☐ Overflow drain pump. Tank water renewal by the principle of density.

ACCESSORIES

- ☐ Manual water softeners
- ☐ Automatic water softeners
- ☐ 400 x 400 mm baskets
- ☐ Inserts & supplements
- ☐ High feet kit
- ☐ Reverse osmosis devices OS-140
- ☐ Detergent dosing equipment for GP glasswashers

SPECIFICATIONS

Basket dimensions: 400 mm x 400 mm

Useful height: 240 mm

Cycle duration: 120 / 150"

Production baskets / hour: 30 / 24

Boiler capacity: 3.2 l

Wash tank capacity: 15 l

Water consumption/cycle: 2.2 l

Loading

- ✓ Pump: 250 W / 0.33 Hp
- ✓ Tank: 1200 W
- ✓ Boiler: 2500 W
- ✓ Total loading: 2750 W

Electrical connection: .

External dimensions (W x D x H)

- ✓ Width: 470 mm
 - ✓ Depth: 535 mm
 - ✓ Height: 670 mm
- Noise level (1m.): <70 dB(A)
- Crated dimensions
525 x 615 x 820 mm

AVAILABLE MODELS

1303050 GP-40 230/50/1

1303051 GP-40 220/60/1

1303054 GP-40B 230/50/1

1303055 GP-40B 220/60/1

* Ask for special versions availability



SAMMIC, S.L. · Basarte, 1
20720 AZKOITIA (Gipuzkoa) · SPAIN

