

ABS | Upright Cabinets

REFRIGERATED UPRIGHT ▶ BLACK PAINTED



GENERAL FEATURES

- 200 Lt. Refrigerated upright
- External in black coated plate, black thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (70mm per side)
- Digital Thermostat
- Independent back-lit main switch (White color)
- Removable Gasket and handle along door profile
- Self closing door, reversible door on request only
- Doors lock fitted as standard
- Adjustable shelves: 2 Pcs + 1 BOTTOM Shelf
- N.2 Adjustable feet + N.2 Rollers at the back
- Energy efficiency class: A

TECHNICAL SPECIFICATIONS

Capacity	200 L
Temperature	+0°C ~ +10°C
Consumption	0.934 kWh/24h
Rated Power	120 W
Noise level	52 dB(A)
Net Weight	37 Kg
Gross Weight	41 Kg
External Dimensions (WxDxH mm)	600x625x853
Internal Dimensions (WxDxH mm)	458x465x603
Packaging dimensions (WxDxH mm)	640x660x890
Loading quantities 20'/40'/40'HQ	54/108/162

CERTIFICATION

CE RoHS



QR 200B



GAS
R600a

A
ENERGY CLASS

4
CLIMATIC CLASS

DETAILS

Main switch and digital thermostat fitted as standard

Foamed door handle

Lock fitted as standard

Shelf with small distance between the line and bottom shelf fitted as standard

Inner assistance fan

PRODUCT DIMENSIONS

